Better Performance On Internally Enhanced Tubes

CLEAN ENHANCED TUBES QUICKLY AND EFFECTIVELY WITH THIS SPECIALLY DESIGNED UNIT.



FEATURES

- > Stainless steel construction
- > Speed control to set shaft rotation at optimum speed for each application
- > Quick connect threadless shaft manifold
- > Interchangeable cleaning tools
- Integrated heavy-duty contractor dolly and large pneumatic tires
- > Simultaneous cleaning solution injection and water power flush up to 500 PSI at 2.2 GP
- > Foot switch activation
- > Reversible shaft rotation



THE PATRIOT

"Patriot" Dual Diameter Nylon Brushes:

"Patriot" Dual Diameter Nylon Brushes are recommended for removing soft deposits (mud, algae, etc.) in straight, ferrous and nonferrous internally enhanced tubes. The large diameter end cleans into the grooves while the small diameter end cleans the lands of a tube's rifling

ENN-062Q

The "Patriot" Dual Diameter Nylon Brush for tubes 5/8" I.D.

ENN-0900

The "Patriot" Dual Diameter Nylon Brush for tubes 15/16" I.D.



Call Us With Your Dirt: 1-800-333-7467

Goodway Technologies Corporation
420 West Avenue, Stamford, CT 06902-6384 U.S.A.
T: 203-359-4708 • F: 203-359-9601 • E: goodway@goodway.com
www.goodway.com



Clean in forward and reverse

The RAM-6 is equipped with a reversible motor for cleaning internally enhanced tubes. The two-direction foot switch permits forward rotation for entering the tubes and reverse rotation for exiting. While the design of the brush and the spiral in the tube cause the brush to be "SELF" propelled through the tube, the variable speed of the RAM-6 allows you to set the flexible shaft speed to match the natural feed rate of the spiral in your tube, preventing slip and allowing the brush to thoroughly clean both the lands and the grooves of the tube.

RAM-6 Service Kit:

Get your RAM-6 working like new with the RAM6-SVC-KIT. This tune-up package includes illustrated instructions as well as all the replacement wear items you will need will need to get your unit running at peak performance.

RAM6-SVC-KIT RAM-6 Service Kit including, 805 0-ring, 6005 Seal, 825 Bearing, 826 Snap Ring, 6020 Snap Ring, 833 Lower Bearing, 6003 Shaft/Driver, 803 Screen Washer, 6006 Back-up Washer, 6012 V Belt and HWST-1037-P Cover Screws (package of six)



Tube Cleaning Solution:

The R6-Cleaner is specifically formulated for use with the RAM-6. It is low foaming and has a neutral pH for non-corrosive cleaning and safe handling. The solution is biodegradable and phosphate free allowing for easy waste disposal. It is free rinsing and will not leave interfering residues. When used in conjunction with the RAM-6, this powerful solution will provide a more thorough cleaning of ferrous and nonferrous tubes.

R6-CLEANER

Tube Cleaning Solution, 1 gallon bottle



Specification	RAM-6
Motor Power	1.5 HP
Input Power	Standard: 15 amps, 115 V, 60 Hz AC Optional: 15 amps, 115 V, 50 Hz; 7.5 amps, 230 V, 60 Hz; or 7.5 amps, 230 V, 50 Hz
Power Supply Cord	21', 14-3 GFCI
Flexible Shaft Speed	Adjustable, 200-800 rpm
Water Requirements	Minimum 25 PSI at 2.2 GPM
Dimensions	46" high x 24" wide x 18" deep
Weight	103 lbs net dry

